

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number  
**WO 2005/054608 A1**

(51) International Patent Classification<sup>7</sup>: **E05B 15/10**,  
15/14, 63/08

(21) International Application Number:  
PCT/GB2004/004342

(22) International Filing Date: 13 October 2004 (13.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0327109.5 21 November 2003 (21.11.2003) GB

(71) Applicant (for all designated States except US): **ARCHITECTURAL PRODUCTS & COMPONENTS**  
[CN/CN]; Factory Building 1, East of High-tech Road 9,  
Qiaonan Area of Xiaoshan Economic & Technological,  
Development Zone, Hangzhou, Zhejiang Province 311231  
(CN).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **NAYLOR, Mark, Anthony** [GB/CN]; No. 201, Unit 2, High Building 2, Huiyu  
Garden, Xiaoshan, Hangzhou, Zhejiang Province (CN).

(74) Agent: **HARRISON GODDARD FOOTE**; Orlando  
House, 11c Compstall Road, Marple Bridge, Stockport  
SK6 5HH (GB).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

[Continued on next page]

(54) Title: A MORTICE LOCK



(57) Abstract: A mortice lock having a deadbolt (16) retained within the lock case (10) and movable between an unlocking position wherein the deadbolt is contained within a lock case, and the locking position in which it extends outwardly therefrom, and a driving mechanism with a cam (18) which connects with and moves the deadbolt between its locking and unlocking positions and a pair of sliding contact members (21, 22) mounted on and slidably movable with respect to the deadbolt between a first position in which it maintains contact with the driving member to effect a full 20mm throw of the deadbolt in one direction, and a second position to enable a full throw of the deadbolt in an opposite direction.



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*